PRODUCT SHEET

FLOOR COVERINGS · CARPET

# Creative Spark 574

**IVC** · Creative Spark



| | |
|---|---|
| FAMILY | **Carpet** |
| BRAND | **IVC** |
| COLLECTION | **Creative Spark** |
| FORMAT | **Tile** |

IVC carpet tile from the Art Intervention collection: in vivid, natural or more neutral shades, Creative Spark answers the decorative trends of commercial interiors, combining individuality and harmony. Pile: tufted 1/10″ structured loop, 100 % solution-dyed polyamide Use: class 33 / LC1, castor chairs in intensive use Fire and acoustics: Bfl-s1, impact sound reduced by 32 dB

## SPECIFICATIONS

| | |
|---|---|
| **Format** | 50 × 50 cm tile, 5 m² box |
| **Structure** | Tufted 1/10″ structured loop pile |
| **Pile composition** | 100 % solution-dyed polyamide |
| **Backing** | EcoFlex™ Statera (modified bitumen, 70 % recycled) |
| **Total weight** | ± 4,100 g/m² |
| **Pile weight** | ± 540 g/m² |
| **Total thickness** | ± 6.3 mm |
| **Pile height** | ± 3.1 mm |
| **Number of tufts** | 176,300 / m² |
| **Use classification (EN 1307)** | 33 / LC1 |
| **Castor chairs (EN ISO 4918)** | A: intensive use |
| **Reaction to fire (EN 13501-1)** | Bfl-s1 |
| **Dimensional stability (EN 986)** | ≤ 0.20 % |
| **Sound absorption (EN ISO 354)** | 0.15 αw |
| **Impact sound (EN ISO 10140-3)** | ΔLw = 32 dB |
| **Antistatic (ISO 6356)** | ≤ 2 kV |
| **Colour fastness to light** | ≥ 7 |
| **GUT-PRODIS number** | 3AA1D4DF |

### Manufacturer documents

- Fiche technique Creative Spark (EN/FR/NL/DE) (MULTI)
- Déclaration de performance Creative Spark (FR)


**Advice, quotes, supply and installation**

Showroom: Aïssat Idir, Petit Staouéli road, Chéraga 16014, Algiers

contact@odecor-dz.com

**+213 770 52 41 12**

Sales department **+213 550 28 23 39**


**Photos, documents and quote**
Scan to open the online page


Characteristics come from the manufacturer's documentation; they are indicative and may change. Document issued on 10/11/2026. · https://odecor-dz.com/en/produits/moquette/creative-spark-574/